




Ball-impact and shock resistant LED safety luminaire with optimised light distribution for the illumination of escape routes. Powder-coated aluminium housing with slim design, perfect for use in environments with high mechanical stresses and in sports facilities.



Technical data

| | | | |
|----------------------------|---------------------------|---------------------------|--|
| Material: | sheet steel powder-coated | Effective power: | 2,7 W |
| Illuminant: | 1 x 1,8W LED-module | Protection class: | III |
| Luminous flux: | 248 lm | Input terminals: | 2.5mm ² feed through wiring |
| Nominal voltage DC: | 24 V ±25 % | Temperature ta: | -15...+40 °C |
| Nominal current DC: | 110 mA | Impact resistance: | IK10 |



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8


| Distance (m) | 5.0 | 6.0 | 7.0 | 8.0 | 9.0 | 10.0 | 11.0 |
|--------------|-----|------|-----|-----|-----|------|------|
| 5.0 | 6.0 | 14.6 | 4.8 | 1.9 | | | |
| 6.0 | 6.2 | 15.8 | 4.9 | 2.1 | | | |
| 7.0 | 6.3 | 16.8 | 5.3 | 2.2 | | | |
| 8.0 | 5.8 | 17.5 | 5.7 | 2.3 | | | |
| 9.0 | 5.4 | 17.9 | 6.0 | 2.3 | | | |
| 10.0 | 4.9 | 17.7 | 6.3 | 2.1 | | | |
| 11.0 | 4.0 | 16.9 | 6.5 | 1.6 | | | |

Articles

SN 8030.2 AP -06 AHB LED 24V

| Colors | RAL 7015 | RAL 9016 | RAL (special) |
|----------|-----------|-----------|---------------|
| Art. no. | 104418577 | 104418678 | 104418779 |


ceiling mounting for exposed wiring Light colour: 4000 K Protection category: IP40



SN 8030.2 D -06 AHB LED 24V

| Colors | RAL 7015 | RAL 9016 | RAL (special) |
|----------|-----------|-----------|---------------|
| Art. no. | 104420395 | 104420496 | 104420500 |

ceiling mounting Light colour: 4000 K Protection category: IP40



| Name | Accessories | Art. no. |
|--|-------------|-----------|
| ILD 24/4-CC-320-C | spare part | 101425321 |
| LM 8030.2 1(6V)/4K AHB 24V RAL9016 LED Modul | spare part | 104487891 |