




Ball-impact and shock resistant LED safety luminaire with optimised light distribution for the illumination of escape routes. Powder-coated aluminium housing with slim design, perfect for use in environments with high mechanical stresses and in sports facilities.



Technical data

Material:	sheet steel powder-coated	Apparent power:	4,4 VA
Illuminant:	1 x 1,8W LED-module	Effective power:	3,6 W
Luminous flux:	248 lm	Inrush current:	8 A / 50 µs
Nominal voltage AC:	230V ±10% 50/60 Hz	Protection class:	I
Nominal voltage DC:	176 - 264 V	Input terminals:	2.5mm ² feed through wiring
Nominal current AC:	19 mA	Temperature ta:	-15...+40 °C
Nominal current DC:	16 mA	Impact resistance:	IK10



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8


Mounting height (m)	5.0	6.0	14.6	4.8	1.9
5.0	6.0	6.2	15.8	4.9	2.1
6.0	6.3	16.8	5.3	2.2	
7.0	5.8	17.5	5.7	2.3	
8.0	5.4	17.9	6.0	2.3	
9.0	4.9	17.7	6.3	2.1	
10.0	4.0	16.9	6.5	1.6	

Articles

SN 8030.2 AP -06 AHB LED J/SV

Colors	RAL 7015	RAL 9016	RAL (special)
Art. no.	104418880	104418981	104419082


ceiling mounting for exposed wiring Light colour: 4000 K Protection category: IP40



SN 8030.2 D -06 AHB LED J/SV

Colors	RAL 7015	RAL 9016	RAL (special)
Art. no.	104444546	102475446	104444647

ceiling mounting Light colour: 4000 K Protection category: IP40



Name	Accessories	Art. no.
J-ET 9/24 SVmax.24VDC,320mAconst	spare part	101420267
LM 8030.2 1(6V)/4K AHB 24V RAL9016 LED Modul	spare part	104487891