


Ball-impact and shock resistant LED safety luminaire with optimised light distribution for the illumination of escape routes. Powder-coated aluminium housing with slim design, perfect for use in environments with high mechanical stresses and in sports facilities.



**Technical data**

<b>Material:</b>	sheet steel powder-coated
<b>Illuminant:</b>	1 x 0,9W LED-module
<b>Luminous flux:</b>	116 lm
<b>Nominal voltage AC:</b>	230V ±10% 50/60 Hz
<b>Nominal voltage DC:</b>	176 - 264 V
<b>Nominal current AC:</b>	13 mA
<b>Nominal current DC:</b>	12 mA

<b>Apparent power:</b>	3,0 VA
<b>Effective power:</b>	2,6 W
<b>Inrush current:</b>	6 A / 22 µs
<b>Protection class:</b>	II
<b>Input terminals:</b>	2.5mm <sup>2</sup> feed through wiring
<b>Temperature ta:</b>	-15...+40 °C
<b>Impact resistance:</b>	IK10



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8


Beam diameter (m)	2.5	3.0	3.5	4.0	4.5
Beam diameter (m)	4.4	4.5	4.4	3.9	2.9
Illuminance (lx)	13.6	13.9	12.6	12.6	12.6
Maintenance factor	4.9	5.0	5.0	4.9	4.7
Minimum illumination (lx)	1.8	1.7	1.5	1.2	0.8

**Articles**

**SN 8030.2 E-03 ALB FLD 230V**


Colors	RAL 7015	RAL 9016	RAL (special)
Art. no.	101831711	101831610	101831812

recessed ceiling mounting    Light colour: 4000 K    Protection category: IP40



**FLD-Supply 230/320 SK II ext.**    Art. no. 101445226

required



Name	Accessories	Art. no.
FLD-Supply 230/320 SK II ext.	required	101445226
LED-Supply 230-3 J-SV SK IIext.	required	101436536
LED-Supply 230-3 NE-SV SK IIext.	required	101436738
LED-Supply 230-3 SK II ext.	required	101436637
LED-Supply 24-3 SK III ext.	required	101442091
LM 8030.2 E 1(3V)/4K ALB 24V RAL9016 LED Modul	spare part	104489410