




Ball-impact and shock resistant LED safety luminaire with optimised light distribution for the illumination of escape routes. Powder-coated aluminium housing with slim design, perfect for use in environments with high mechanical stresses and in sports facilities.



Technical data

Material:	sheet steel powder-coated
Illuminant:	1 x 0,9W LED-module
Luminous flux:	116 lm
Nominal voltage DC:	24 V $\pm$ 20 %
Nominal current DC:	65 mA

Effective power:	1,6 W
Protection class:	III
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C
Impact resistance:	IK10




Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

2.5	4.4	13.6	4.9	1.8
3.0	4.5	13.9	5.0	1.7
3.5	4.4	12.6	5.0	1.5
4.0	3.9	12.6	4.9	1.2
4.5	2.9	12.6	4.7	0.8

Articles

SN 8030.2 E -03 ALB LED 24V


Colors	RAL 7015	RAL 9016	RAL (special)
Art. no.	101831711	101831610	101831812
recessed ceiling mounting Light colour: 4000 K Protection category: IP40			



LED-Supply 24-3 SK III ext.

Art. no. 101442091

required



Name	Accessories	Art. no.
FLD-Supply 230/320 SK II ext.	required	101445226
LED-Supply 230-3 J-SV SK II ext.	required	101436536
LED-Supply 230-3 NE-SV SK II ext.	required	101436738
LED-Supply 230-3 SK II ext.	required	101436637
LED-Supply 24-3 SK III ext.	required	101442091
LM 8030.2 E 1(3V)/4K ALB 24V RAL9016 LED Modul	spare part	104489410