


Ball-impact and shock resistant LED safety luminaire with optimised light distribution for the illumination of escape routes. Powder-coated aluminium housing with slim design, perfect for use in environments with high mechanical stresses and in sports facilities.



Technical data

Material:	sheet steel powder-coated	Apparent power:	3,5 VA
Illuminant:	1 x 0,9W LED-module	Effective power:	2,6 W
Luminous flux:	116 lm	Inrush current:	8 A / 50 µs
Nominal voltage AC:	230V ±10% 50/60 Hz	Protection class:	II
Nominal voltage DC:	176 - 264 V	Input terminals:	2.5mm ² feed through wiring
Nominal current AC:	15 mA	Temperature ta:	-15...+40 °C
Nominal current DC:	12 mA	Impact resistance:	IK10



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8


Beam diameter (m)	2.5	3.0	3.5	4.0	4.5
Beam diameter (m)	2.5	3.0	3.5	4.0	4.5
Illuminance (lx)	4.4	3.0	2.2	1.7	1.3
Beam diameter (m)	13.6	10.0	7.4	5.8	4.5
Illuminance (lx)	4.9	3.5	2.6	2.0	1.5
Beam diameter (m)	1.8	2.2	2.9	3.7	4.5
Illuminance (lx)	1.7	2.2	2.9	3.7	4.5
Beam diameter (m)	1.5	1.9	2.5	3.2	4.0
Illuminance (lx)	1.2	1.5	2.0	2.6	3.3
Beam diameter (m)	0.8	1.0	1.3	1.7	2.1
Illuminance (lx)	0.8	1.0	1.3	1.7	2.1

Articles

SN 8030.2 E-03 ALB LED J/SV

Colors	RAL 7015	RAL 9016	RAL (special)
Art. no.	101831711	101831610	101831812


recessed ceiling mounting Light colour: 4000 K Protection category: IP40



LED-Supply 230-3 J-SV SK IIext.

Art. no. 101436536

required



Name	Accessories	Art. no.
FLD-Supply 230/320 SK II ext.	required	101445226
LED-Supply 230-3 J-SV SK IIext.	required	101436536
LED-Supply 230-3 NE-SV SK IIext.	required	101436738
LED-Supply 230-3 SK II ext.	required	101436637
LED-Supply 24-3 SK III ext.	required	101442091
LM 8030.2 E 1(3V)/4K ALB 24V RAL9016 LED Modul	spare part	104489410