



Ball-impact and shock resistant LED safety luminaire with optimised light distribution for the illumination of areas. Powder-coated aluminium housing with slim design, perfect for use in environments with high mechanical stresses and in sports facilities.



Technical data

Material:	sheet steel powder-coated
Illuminant:	1 x 3,5W LED-module
Luminous flux:	491 lm
Nominal voltage AC:	230V ±10% 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	33 mA
Nominal current DC:	25 mA

Apparent power:	7,6 VA
Effective power:	5,7 W
Inrush current:	8 A / 50 µs
Protection class:	III
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C
Impact resistance:	IK10



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

5.5	6.4	15.9
6.0	6.6	16.5
6.5	6.7	17.1
7.0	6.7	17.6
7.5	6.7	18.0
8.0	6.5	18.3
8.5	6.3	18.6
9.0	5.9	18.8
9.5	5.4	19.0
10.0	4.8	19.0

Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8


5.5	4.7	12.9
6.0	4.9	13.6
6.5	4.9	13.7
7.0	4.9	14.7
7.5	4.8	15.4
8.0	4.8	15.8
8.5	4.7	15.9
9.0	4.6	16.2
9.5	4.5	16.6
10.0	4.2	17.0

Articles

SN 8030.2 E -12 SHB LED J/SV

Colors	RAL 7015	RAL 9016	RAL (special)
Art. no.	104240846	104240745	104240947


recessed ceiling mounting Light colour: 4000 K Protection category: IP40



LED-Supply 230-3 J-SV SK IIext.

Art. no. 101436536

required



Name	Accessories	Art. no.
FLD-Supply 230/320 SK II ext.	required	101445226
LED-Supply 230-3 J-SV SK IIext.	required	101436536
LED-Supply 230-3 NE-SV SK IIext.	required	101436738
LED-Supply 230-3 SK II ext.	required	101436637
LED-Supply 24-3 SK III ext.	required	101442091
LM 8030.2 E 1(12V)/4K SHB 24V RAL9016 LED Modul	spare part	104489511