


Ball-impact and shock resistant safety luminaires with state-of-the-art LED-technology for area or escape route illumination. Powder-coated aluminium housing with slim design, perfect for use in environments with high mechanical stresses and in sports facilities.



### Technical data

<b>Material:</b>	sheet steel powder-coated	<b>Protection class:</b>	III
<b>Illuminant:</b>	4 x 1W LED-module	<b>Input terminals:</b>	2.5mm <sup>2</sup> feed through wiring
<b>Luminous flux:</b>	310 lm	<b>Temperature ta:</b>	-15...+40 °C
<b>Nominal voltage DC:</b>	24 V ±20 %	<b>Impact resistance:</b>	IK10
<b>Nominal current DC:</b>	200 mA		



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

[m]	2.5	3.7	8.5
2.5	3.7	4.1	9.7
3.0	4.0	4.7	11.5
4.0	5.0	5.0	12.9
5.0	5.1	4.9	13.9
6.0	4.5	3.7	14.3
7.0	2.5	2.5	13.8
8.0			
9.0			
10.0			

Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8


[m]	2.5	2.7	6.4
2.5	3.1	3.1	7.3
3.0	4.0	3.6	9.0
4.0	5.0	3.7	10.6
5.0	6.0	3.7	11.8
6.0	7.0	3.6	12.4
7.0	8.0	3.4	12.8
8.0	9.0	3.1	12.6
9.0	10.0	2.6	12.4

### Articles

#### SN 8030 E LED 24V


Colors	RAL 7015	RAL 9016	RAL (special)
Art. no.	101311951	101311850	101312052

recessed ceiling mounting      Light colour: 6500 K      Protection category: IP40



#### LED-Supply 24-3 SK III ext.

Art. no. 101442091



Name	Accessories	Art. no.
LED-Supply 230-3 J-SV SK IIext.	required	101436536
LED-Supply 230-3 NE-SV SK IIext.	required	101436738
LED-Supply 230-3 SK II ext.	required	101436637
LED-Supply 24-3 SK III ext.	required	101442091