


Ball-impact and shock resistant safety luminaires with state-of-the-art LED-technology for area or escape route illumination. Powder-coated aluminium housing with slim design, perfect for use in environments with high mechanical stresses and in sports facilities.



Technical data

Material:	sheet steel powder-coated
Illuminant:	4 x 1W LED-module
Luminous flux:	310 lm
Nominal voltage DC:	24 V ±20 %
Nominal current DC:	200 mA

Protection class:	III
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C
Impact resistance:	IK10



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

Beam diameter [m]	Beam height [m]	Beam diameter [m]	Beam height [m]
2.5	3.7	8.5	
3.0	4.1	9.7	
4.0	4.7	11.5	
5.0	5.0	12.9	
6.0	5.1	13.9	
7.0	4.9	14.3	
8.0	4.5	14.4	
9.0	3.7	14.3	
10.0	2.5	13.8	

Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8


Beam diameter [m]	Beam height [m]	Beam diameter [m]	Beam height [m]
2.5	2.7	6.4	
3.0	3.1	7.3	
4.0	3.6	9.0	
5.0	3.7	10.6	
6.0	3.7	11.8	
7.0	3.6	12.4	
8.0	3.4	12.8	
9.0	3.1	12.6	
10.0	2.6	12.4	

Articles

SN 8030 AP LED 24V

Colors	RAL 7015	RAL 9016	RAL (special)
Art. no.	100835035	101355296	100835136

ceiling mounting for exposed wiring Light colour: 6500 K Protection category: IP40



SN 8030 D LED 24V

Colors	RAL 7015	RAL 9016	RAL (special)
Art. no.	101355094	101354993	101355195

ceiling mounting Light colour: 6500 K Protection category: IP40

