




Robust LED safety luminaire with optimised light distribution for the illumination of escape routes. Brushed stainless steel luminaire with high degree of protection. Suitable for use in food industry or food processing plants with high demands on product hygiene.



Technical data

Material:	stainless steel
Illuminant:	1 x 0,9W LED-module
Luminous flux:	116 lm
Nominal voltage AC:	230V ±10% 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	13 mA
Nominal current DC:	12 mA

Apparent power:	3,0 VA
Effective power:	2,6 W
Inrush current:	6 A / 22 µs
Protection class:	I
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C
Impact resistance:	IK10



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8


Beam diameter (m)	2.5	3.0	3.5	4.0	4.5
2.5	4.4	13.6	4.9	1.8	
3.0	4.5	13.9	5.0	1.7	
3.5	4.4	12.6	5.0	1.5	
4.0	3.9	12.6	4.9	1.2	
4.5	2.9	12.6	4.7	0.8	

Articles

SN 804.2 AP -03 ALB FLD 230V

Colors	stainless steel	RAL 9016	HWF (special)	RAL (special)
Art. no.	101881524	101881726	101881625	101881827



ceiling mounting for exposed wiring Light colour: 4000 K Protection category: IP65




SN 804.2 D -03 ALB FLD 230V

Colors	stainless steel	RAL 9016	HWF (special)	RAL (special)
Art. no.	101881120	101881322	101881221	101881423

ceiling mounting Light colour: 4000 K Protection category: IP65



Ceiling recessed frame SN 804.2 D Art. no. 102022374



Name	Accessories	Art. no.
Ceiling recessed frame SN 804.2 D	optional	102022374
FLD 230/8 – CC – 320 – C	spare part	100903238