


Robust LED safety luminaire with optimised light distribution for the illumination of escape routes. Brushed stainless steel luminaire with high degree of protection. Suitable for use in food industry or food processing plants with high demands on product hygiene.



Technical data

Material:	stainless steel
Illuminant:	1 x 0,9W LED-module
Luminous flux:	116 lm
Nominal voltage DC:	24 V ±25 %
Nominal current DC:	80 mA

Effective power:	2,0 W
Protection class:	III
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C
Impact resistance:	IK10




Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

lm	□ 2.5	□ 3.0	□ 3.5	□ 4.0	□ 4.5
2.5	4.4	13.6	4.9	1.8	
3.0	4.5	13.9	5.0	1.7	
3.5	4.4	12.6	5.0	1.5	
4.0	3.9	12.6	4.9	1.2	
4.5	2.9	12.6	4.7	0.8	

Articles


SN 804.2 AP -03 ALB LED 24V				
Colors	stainless steel	RAL 9016	HWF (special)	RAL (special)
Art. no.	101877682	101877884	101877783	101877985

ceiling mounting for exposed wiring Light colour: 4000 K Protection category: IP65




SN 804.2 D -03 ALB LED 24V				
Colors	stainless steel	RAL 9016	HWF (special)	RAL (special)
Art. no.	101877278	101877480	101877379	101877581

ceiling mounting Light colour: 4000 K Protection category: IP65



Ceiling recessed frame SN 804.2 D	Art. no. 102022374
--	--------------------



Name	Accessories	Art. no.
Ceiling recessed frame SN 804.2 D	optional	102022374
ILD 24/4-CC-320-C	spare part	101425321