




Robust LED safety luminaire with optimised light distribution for the illumination of escape routes. Brushed stainless steel luminaire with high degree of protection. Suitable for use in food industry or food processing plants with high demands on product hygiene.



### Technical data

<b>Material:</b>	stainless steel	<b>Apparent power:</b>	3,5 VA
<b>Illuminant:</b>	1 x 0,9W LED-module	<b>Effective power:</b>	2,6 W
<b>Luminous flux:</b>	116 lm	<b>Inrush current:</b>	8 A / 50 µs
<b>Nominal voltage AC:</b>	230V ±10% 50/60 Hz	<b>Protection class:</b>	I
<b>Nominal voltage DC:</b>	176 - 264 V	<b>Input terminals:</b>	2.5mm <sup>2</sup> feed through wiring
<b>Nominal current AC:</b>	15 mA	<b>Temperature ta:</b>	-15...+40 °C
<b>Nominal current DC:</b>	12 mA	<b>Impact resistance:</b>	IK10



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8


Beam diameter (m)	2.5	3.0	3.5	4.0	4.5
Beam diameter (m)	2.5	3.0	3.5	4.0	4.5
Illuminance (lx)	13.6	13.9	12.6	12.6	12.6
Maintenance factor	4.9	5.0	5.0	4.9	4.7
Maintenance factor	1.8	1.7	1.5	1.2	0.8

### Articles

#### SN 804.2 AP -03 ALB LED J/SV

Colors	stainless steel	RAL 9016	HWF (special)	RAL (special)
Art. no.	101860508	101885968	101884049	101884150


ceiling mounting for exposed wiring Light colour: 4000 K Protection category: IP65



#### SN 804.2 D -03 ALB LED J/SV

Colors	stainless steel	RAL 9016	HWF (special)	RAL (special)
Art. no.	101860407	101885867	101883847	101883948

ceiling mounting Light colour: 4000 K Protection category: IP65



#### Ceiling recessed frame SN 804.2 D

Art. no. 102022374

Name	Accessories	Art. no.
Ceiling recessed frame SN 804.2 D	optional	102022374
J-ET 9/24 SVmax.24VDC,320mAconst	spare part	101420267

