




Robust LED safety luminaire with optimised light distribution for the illumination of escape routes with high mounting heights. Also suitable for illumination of firefighting and fire alarm systems as well as first aid stations with 5 lx vertical illuminance. Brushed stainless steel luminaire with high degree of protection. Suitable for use in food industry or food processing plants with high demands on product hygiene.



Technical data

Material:	stainless steel
Illuminant:	1 x 1,8W LED-module
Luminous flux:	248 lm
Nominal voltage AC:	230V ±10% 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	17 mA
Nominal current DC:	16 mA

Apparent power:	3,9 VA
Effective power:	3,6 W
Inrush current:	6 A / 22 µs
Protection class:	I
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C
Impact resistance:	IK10




Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

Mounting height (m)	1.0m	1.5m	2.0m	2.5m	3.0m
5.0	6.0	14.6	4.8	1.9	
6.0	6.2	15.8	4.9	2.1	
7.0	6.3	16.8	5.3	2.2	
8.0	5.8	17.5	5.7	2.3	
9.0	5.4	17.9	6.0	2.3	
10.0	4.9	17.7	6.3	2.1	
11.0	4.0	16.9	6.5	1.6	

Articles


SN 804.2 AP -06 AHB FLD 230V				
Colors	stainless steel	RAL 9016	HWF (special)	RAL (special)
Art. no.	101882231	101885160	101882332	101882433

ceiling mounting for exposed wiring Light colour: 4000 K Protection category: IP65




SN 804.2 D -06 AHB FLD 230V				
Colors	stainless steel	RAL 9016	HWF (special)	RAL (special)
Art. no.	101881928	101885059	101882029	101882130

ceiling mounting Light colour: 4000 K Protection category: IP65



Ceiling recessed frame SN 804.2 D	Art. no. 102022374
-----------------------------------	--------------------



Name	Accessories	Art. no.
Ceiling recessed frame SN 804.2 D	optional	102022374
FLD 230/8 – CC – 320 – C	spare part	100903238