




Robust LED safety luminaire with optimised light distribution for the illumination of escape routes with high mounting heights. Also suitable for illumination of firefighting and fire alarm systems as well as first aid stations with 5 lx vertical illuminance. Brushed stainless steel luminaire with high degree of protection. Suitable for use in food industry or food processing plants with high demands on product hygiene.



### Technical data

<b>Material:</b>	stainless steel	<b>Effective power:</b>	2,7 W
<b>Illuminant:</b>	1 x 1,8W LED-module	<b>Protection class:</b>	III
<b>Luminous flux:</b>	248 lm	<b>Input terminals:</b>	2.5mm <sup>2</sup> feed through wiring
<b>Nominal voltage DC:</b>	24 V ±25 %	<b>Temperature ta:</b>	-15...+40 °C
<b>Nominal current DC:</b>	110 mA	<b>Impact resistance:</b>	IK10



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8


Mounting height (m)	1.0m	1.5m	2.0m	2.5m	3.0m
5.0	6.0	14.6	4.8	1.9	
6.0	6.2	15.8	4.9	2.1	
7.0	6.3	16.8	5.3	2.2	
8.0	5.8	17.5	5.7	2.3	
9.0	5.4	17.9	6.0	2.3	
10.0	4.9	17.7	6.3	2.1	
11.0	4.0	16.9	6.5	1.6	

### Articles

#### SN 804.2 AP -06 AHB LED 24V

Colors	stainless steel	RAL 9016	HWF (special)	RAL (special)
Art. no.	101878490	101878692	101878591	101878793


ceiling mounting for exposed wiring Light colour: 4000 K Protection category: IP65



#### SN 804.2 D -06 AHB LED 24V


Colors	stainless steel	RAL 9016	HWF (special)	RAL (special)
Art. no.	101878086	101878288	101878187	101878389

ceiling mounting Light colour: 4000 K Protection category: IP65



#### Ceiling recessed frame SN 804.2 D

Art. no. 102022374



Name	Accessories	Art. no.
Ceiling recessed frame SN 804.2 D	optional	102022374
ILD 24/4-CC-320-C	spare part	101425321