




Robust LED safety luminaire with optimised light distribution for the illumination of areas with high mounting heights. Brushed stainless steel luminaire with high degree of protection. Suitable for use in food industry or food processing plants with high demands on product hygiene.



Technical data

Material:	stainless steel
Illuminant:	1 x 3,5W LED-module
Luminous flux:	491 lm
Nominal voltage AC:	230V ±10% 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	25 mA
Nominal current DC:	25 mA

Apparent power:	5,8 VA
Effective power:	5,5 W
Inrush current:	6 A / 22 µs
Protection class:	I
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C
Impact resistance:	IK10



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

	5.5	6.4	15.9
	6.0	6.6	16.5
	6.5	6.7	17.1
	7.0	6.7	17.6
	7.5	6.7	18.0
	8.0	6.5	18.3
	8.5	6.3	18.6
	9.0	5.9	18.8
	9.5	5.4	19.0
	10.0	4.8	19.0

Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8


	5.5	4.7	12.9
	6.0	4.9	13.6
	6.5	4.9	13.7
	7.0	4.9	14.7
	7.5	4.8	15.4
	8.0	4.8	15.8
	8.5	4.7	15.9
	9.0	4.6	16.2
	9.5	4.5	16.6
	10.0	4.2	17.0

Articles

SN 804.2 AP -12 SHB FLD 230V

Colors	stainless steel	RAL 9016	HWF (special)	RAL (special)
Art. no.	101880716	101880918	101880817	101881019


ceiling mounting for exposed wiring Light colour: 4000 K Protection category: IP65




SN 804.2 D -12 SHB FLD 230V

Colors	stainless steel	RAL 9016	HWF (special)	RAL (special)
Art. no.	101880312	101880514	101880413	101880615

ceiling mounting Light colour: 4000 K Protection category: IP65



Ceiling recessed frame SN 804.2 D Art. no. 10202374



Name	Accessories	Art. no.
Ceiling recessed frame SN 804.2 D	optional	10202374
FLD 230/8 – CC – 320 – C	spare part	100903238