




Robust LED safety luminaire with optimised light distribution for the illumination of areas with high mounting heights. Brushed stainless steel luminaire with high degree of protection. Suitable for use in food industry or food processing plants with high demands on product hygiene.



Technical data

Material:	stainless steel
Illuminant:	1 x 3,5W LED-module
Luminous flux:	491 lm
Nominal voltage DC:	24 V ±25 %
Nominal current DC:	190 mA

Effective power:	4,6 W
Protection class:	III
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C
Impact resistance:	IK10



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

Height (m)	Beam diameter (mm)	Beam diameter (mm)
5.5	6.4	15.9
6.0	6.6	16.5
6.5	6.7	17.1
7.0	6.7	17.6
7.5	6.7	18.0
8.0	6.5	18.3
8.5	6.3	18.6
9.0	5.9	18.8
9.5	5.4	19.0
10.0	4.8	19.0


Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8

Height (m)	Beam diameter (mm)	Beam diameter (mm)
5.5	4.7	12.9
6.0	4.9	13.6
6.5	4.9	13.7
7.0	4.9	14.7
7.5	4.8	15.4
8.0	4.8	15.8
8.5	4.7	15.9
9.0	4.6	16.2
9.5	4.5	16.6
10.0	4.2	17.0

Articles


SN 804.2 AP -12 SHB LED 24V				
Colors	stainless steel	RAL 9016	HWF (special)	RAL (special)
Art. no.	101876874	101877076	101876975	101877177

ceiling mounting for exposed wiring Light colour: 4000 K Protection category: IP65




SN 804.2 D -12 SHB LED 24V				
Colors	stainless steel	RAL 9016	HWF (special)	RAL (special)
Art. no.	101858989	101876672	101876571	101876773

ceiling mounting Light colour: 4000 K Protection category: IP65



Ceiling recessed frame SN 804.2 D	Art. no. 102022374
--	--------------------



Name	Accessories	Art. no.
Ceiling recessed frame SN 804.2 D	optional	102022374
ILD 24/4-CC-320-C	spare part	101425321