




Robust LED safety luminaire with optimised light distribution for the illumination of areas with high mounting heights. Brushed stainless steel luminaire with high degree of protection. Suitable for use in food industry or food processing plants with high demands on product hygiene.



Technical data

Material:	stainless steel
Illuminant:	1 x 3,5W LED-module
Luminous flux:	491 lm
Nominal voltage AC:	230V ±10% 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	33 mA
Nominal current DC:	25 mA

Apparent power:	7,6 VA
Effective power:	5,7 W
Inrush current:	8 A / 50 µs
Protection class:	I
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C
Impact resistance:	IK10



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

Mounting height (m)	5.5	6.4	15.9
5.5	6.0	6.6	16.5
6.5	6.5	6.7	17.1
7.0	6.7	6.7	17.6
7.5	6.7	6.7	18.0
8.0	6.5	6.5	18.3
8.5	6.3	6.3	18.6
9.0	5.9	5.9	18.8
9.5	5.4	5.4	19.0
10.0	4.8	4.8	19.0

Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8


Mounting height (m)	5.5	4.7	12.9
6.0	4.9	4.9	13.6
6.5	4.9	4.9	13.7
7.0	4.9	4.9	14.7
7.5	4.8	4.8	15.4
8.0	4.8	4.8	15.8
8.5	4.7	4.7	15.9
9.0	4.6	4.6	16.2
9.5	4.5	4.5	16.6
10.0	4.2	4.2	17.0

Articles

SN 804.2 AP -12 SHB LED J/SV

Colors	stainless steel	RAL 9016	HWF (special)	RAL (special)
Art. no.	101860306	101885766	101883645	101883746


ceiling mounting for exposed wiring Light colour: 4000 K Protection category: IP65



SN 804.2 D -12 SHB LED J/SV


Colors	stainless steel	RAL 9016	HWF (special)	RAL (special)
Art. no.	101860205	101885665	101883443	101883544

ceiling mounting Light colour: 4000 K Protection category: IP65



Ceiling recessed frame SN 804.2 D

Art. no. 102022374



Name	Accessories	Art. no.
Ceiling recessed frame SN 804.2 D	optional	102022374
J-ET 9/24 SVmax.24VDC,320mAconst	spare part	101420267