




Robust LED safety luminaire with optimised light distribution for the illumination of areas. Brushed stainless steel luminaire with high degree of protection. Suitable for use in food industry or food processing plants with high demands on product hygiene.



**Technical data**

<b>Material:</b>	stainless steel
<b>Illuminant:</b>	1 x 3,5W LED-module
<b>Luminous flux:</b>	434 lm
<b>Nominal voltage AC:</b>	230V ±10% 50/60 Hz
<b>Nominal voltage DC:</b>	176 - 264 V
<b>Nominal current AC:</b>	25 mA
<b>Nominal current DC:</b>	25 mA

<b>Apparent power:</b>	5,8 VA
<b>Effective power:</b>	5,5 W
<b>Inrush current:</b>	6 A / 22 µs
<b>Protection class:</b>	I
<b>Input terminals:</b>	2.5mm <sup>2</sup> feed through wiring
<b>Temperature ta:</b>	-15...+40 °C
<b>Impact resistance:</b>	IK10



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

2.5	5.3	13.4
3.0	5.4	14.2
3.5	5.5	15.0
4.0	5.5	15.1
4.5	5.4	15.5
5.0	5.0	15.5

Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8


2.5	4.4	11.8
3.0	4.5	13.0
3.5	4.4	13.9
4.0	4.3	14.4
4.5	3.8	14.9
5.0	3.4	15.3

**Articles**

**SN 804.2 AP -12 SLB FLD 230V**

Colors	stainless steel	RAL 9016	HWF (special)	RAL (special)
Art. no.	101879504	101879706	101879605	101879807


ceiling mounting for exposed wiring Light colour: 4000 K Protection category: IP65




**SN 804.2 D -12 SLB FLD 230V**

Colors	stainless steel	RAL 9016	HWF (special)	RAL (special)
Art. no.	101879100	101879302	101879201	101879403

ceiling mounting Light colour: 4000 K Protection category: IP65



**Ceiling recessed frame SN 804.2 D** Art. no. 10202374



Name	Accessories	Art. no.
Ceiling recessed frame SN 804.2 D	optional	10202374
FLD 230/8 – CC – 320 – C	spare part	100903238