




Robust LED safety luminaire with optimised light distribution for the illumination of areas. Brushed stainless steel luminaire with high degree of protection. Suitable for use in food industry or food processing plants with high demands on product hygiene.



Technical data

Material:	stainless steel	Effective power:	4,6 W
Illuminant:	1 x 3,5W LED-module	Protection class:	III
Luminous flux:	434 lm	Input terminals:	2.5mm ² feed through wiring
Nominal voltage DC:	24 V ±25 %	Temperature ta:	-15...+40 °C
Nominal current DC:	190 mA	Impact resistance:	IK10



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

Distance (m)	2.5	5.3	13.4
2.5	3.0	5.4	14.2
3.5	3.5	5.5	15.0
4.0	4.0	5.5	15.1
4.5	4.5	5.4	15.5
5.0	5.0	5.0	15.5

Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8


Distance (m)	2.5	4.4	11.8
2.5	3.0	4.5	13.0
3.5	3.5	4.4	13.9
4.0	4.0	4.3	14.4
4.5	4.5	3.8	14.9
5.0	5.0	3.4	15.3

Articles

SN 804.2 AP -12 SLB LED 24V

Colors	stainless steel	RAL 9016	HWF (special)	RAL (special)
Art. no.	101875763	101875965	101875864	101876066


ceiling mounting for exposed wiring Light colour: 4000 K Protection category: IP65



SN 804.2 D -12 SLB LED 24V


Colors	stainless steel	RAL 9016	HWF (special)	RAL (special)
Art. no.	101875460	101872834	101875561	101875662

ceiling mounting Light colour: 4000 K Protection category: IP65



Ceiling recessed frame SN 804.2 D

Art. no. 102022374



Name	Accessories	Art. no.
Ceiling recessed frame SN 804.2 D	optional	102022374
ILD 24/4-CC-320-C	spare part	101425321