




Robust LED safety luminaire with optimised light distribution for the illumination of areas. Brushed stainless steel luminaire with high degree of protection. Suitable for use in food industry or food processing plants with high demands on product hygiene.



Technical data

Material:	stainless steel
Illuminant:	1 x 3,5W LED-module
Luminous flux:	434 lm
Nominal voltage AC:	230V ±10% 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	33 mA
Nominal current DC:	25 mA

Apparent power:	7,6 VA
Effective power:	5,7 W
Inrush current:	8 A / 50 µs
Protection class:	I
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C
Impact resistance:	IK10



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

2.5	5.3	13.4
3.0	5.4	14.2
3.5	5.5	15.0
4.0	5.5	15.1
4.5	5.4	15.5
5.0	5.0	15.5

Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8


2.5	4.4	11.8
3.0	4.5	13.0
3.5	4.4	13.9
4.0	4.3	14.4
4.5	3.8	14.9
5.0	3.4	15.3

Articles

SN 804.2 AP -12 SLB LED J/SV

Colors	stainless steel	RAL 9016	HWF (special)	RAL (special)
Art. no.	101860003	101885463	101883039	101883140


ceiling mounting for exposed wiring Light colour: 4000 K Protection category: IP65




SN 804.2 D -12 SLB LED J/SV

Colors	stainless steel	RAL 9016	HWF (special)	RAL (special)
Art. no.	101859902	101885362	101882837	101882938

ceiling mounting Light colour: 4000 K Protection category: IP65



Ceiling recessed frame SN 804.2 D Art. no. 102022374



Name	Accessories	Art. no.
Ceiling recessed frame SN 804.2 D	optional	102022374
J-ET 9/24 SVmax.24VDC,320mAconst	spare part	101420267