




Robust LED safety luminaire with optimised light distribution for the illumination of areas with high mounting heights up to 24m. Brushed stainless steel luminaire with high degree of protection. Suitable for use in food industry or food processing plants with high demands on product hygiene. Lockable mounting bracket to align to the area to be illuminated.



### Technical data

<b>Material:</b>	stainless steel	<b>Effective power:</b>	4,6 W
<b>Illuminant:</b>	1 x 3,5W LED-module	<b>Protection class:</b>	III
<b>Luminous flux:</b>	403 lm	<b>Input terminals:</b>	2.5mm <sup>2</sup> feed through wiring
<b>Nominal voltage DC:</b>	24 V ±25 %	<b>Temperature ta:</b>	-15...+40 °C
<b>Nominal current DC:</b>	190 mA		



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

Mounting height (m)	10	12	14	16	18	20	22	24
10	4.9							
12	4.7	14.1						
14	4.8	13.8						
16	4.8	13.4						
18	4.8	13.5						
20	4.7	13.6						
22	4.4	13.7						
24	3.5	13.6						

Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8

Mounting height (m)	10	12	14	16	18	20	22	24
10	3.5	10.9						
12	3.6	10.9						
14	3.6	11.4						
16	3.5	12.2						
18	3.5	12.6						
20	3.5	12.6						
22	3.5	12.6						
24	3.4	12.7						

### Articles

SN 804.2 W -12 SUHB LED 24V					Name	Accessories	Art. no.
Colors	stainless steel	RAL 9016	HWF (special)	RAL (special)	ILD 24/4-CC-320-C	spare part	101425321
Art. no.	101878894	101879096	101878995	101362673			

wall bracket mounting      Light colour: 4000 K      Protection category: IP65

