




Robust LED safety luminaire with optimised light distribution for the illumination of areas with high mounting heights up to 24m. Brushed stainless steel luminaire with high degree of protection. Suitable for use in food industry or food processing plants with high demands on product hygiene. Lockable mounting bracket to align to the area to be illuminated.



### Technical data

<b>Material:</b>	stainless steel	<b>Apparent power:</b>	7,6 VA
<b>Illuminant:</b>	1 x 3,5W LED-module	<b>Effective power:</b>	5,7 W
<b>Luminous flux:</b>	403 lm	<b>Inrush current:</b>	8 A / 50 µs
<b>Nominal voltage AC:</b>	230V ±10% 50/60 Hz	<b>Protection class:</b>	I
<b>Nominal voltage DC:</b>	176 - 264 V	<b>Input terminals:</b>	2.5mm <sup>2</sup> feed through wiring
<b>Nominal current AC:</b>	33 mA	<b>Temperature ta:</b>	-15...+40 °C
<b>Nominal current DC:</b>	25 mA		



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

Mounting height (m)	10°	15°	20°
10	4.9	13.6	
12	4.7	14.1	
14	4.8	13.8	
16	4.8	13.4	
18	4.8	13.5	
20	4.7	13.6	
22	4.4	13.7	
24	3.5	13.6	

Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8

Mounting height (m)	10°	15°	20°
10	3.5	10.9	
12	3.6	10.9	
14	3.6	11.4	
16	3.5	12.2	
18	3.5	12.6	
20	3.5	12.6	
22	3.5	12.6	
24	3.4	12.7	

### Articles

SN 804.2 W -12 SUHB LED J/SV					Name	Accessories	Art. no.
Colors	stainless steel	RAL 9016	HWF (special)	RAL (special)	J-ET 9/24 SVmax.24VDC,320mAconst	spare part	101420267
Art. no.	101860811	101886271	101884655	101884756			

wall bracket mounting      Light colour: 4000 K      Protection category: IP65

