




Robust LED safety luminaire with optimised light distribution for the illumination of escape routes with high mounting heights. Also suitable for illumination of firefighting and fire alarm systems as well as first aid stations with 5 lx vertical illuminance. Brushed stainless steel luminaire with high degree of protection. Suitable for use in food industry or food processing plants with high demands on product hygiene.



Technical data

Material:	stainless steel	Apparent power:	3,9 VA
Illuminant:	1 x 1,8W LED-module	Effective power:	3,6 W
Nominal voltage AC:	230V ±10% 50/60 Hz	Inrush current:	6 A / 22 µs
Nominal voltage DC:	176 - 264 V	Protection class:	I
Nominal current AC:	17 mA	Input terminals:	2.5mm² feed through wiring
Nominal current DC:	16 mA	Temperature ta:	-15...+40 °C



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

[m]	5.0	6.0	14.6	4.8	1.9
5.0	6.0	14.6	4.8	1.9	
6.0	6.2	15.8	4.9	2.1	
7.0	6.3	16.8	5.3	2.2	
8.0	5.8	17.5	5.7	2.3	
9.0	5.4	17.9	6.0	2.3	
10.0	4.9	17.7	6.3	2.1	
11.0	4.0	16.9	6.5	1.6	

Articles

SN 804.2 W -06 AHB FLD 230V

Colors	stainless steel	RAL 9016	HWf (special)	RAL (special)
Art. no.	104518005	104518914	104518106	104518207

wall bracket mounting Light colour: 4000 K

Protection category: IP65

