

24V

SN 804.2 W-06 AHB Stainless steel luminaires


For connection to INOTEC systems with 24V circuits



Robust LED safety luminaire with optimised light distribution for the illumination of escape routes with high mounting heights. Also suitable for illumination of firefighting and fire alarm systems as well as first aid stations with 5 lx vertical illuminance. Brushed stainless steel luminaire with high degree of protection. Suitable for use in food industry or food processing plants with high demands on product hygiene.

**Technical data**

Material:	stainless steel	Protection class:	III
Illuminant:	1 x 1,8W LED-module	Input terminals:	2.5mm ² feed through wiring
Nominal voltage DC:	24 V ±25 %	Temperature ta:	-15...+40 °C
Nominal current DC:	110 mA		



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

Distance [m]	1.0	2.0	3.0	4.0	5.0
5.0	6.0	14.6	4.8	1.9	
6.0	6.2	15.8	4.9	2.1	
7.0	6.3	16.8	5.3	2.2	
8.0	5.8	17.5	5.7	2.3	
9.0	5.4	17.9	6.0	2.3	
10.0	4.9	17.7	6.3	2.1	
11.0	4.0	16.9	6.5	1.6	

Articles

SN 804.2 W -06 AHB LED 24V				
Colors	stainless steel	RAL 9016	HWF (special)	RAL (special)
Art. no.	104517092	104517294	104517193	104517395

wall bracket mounting Light colour: 4000 K

Protection category: IP65

