

230V

J/SV

SN 804.2 W-06 AHB Stainless steel luminaires


For connection to JOKER-central battery systems



Robust LED safety luminaire with optimised light distribution for the illumination of escape routes with high mounting heights. Also suitable for illumination of firefighting and fire alarm systems as well as first aid stations with 5 lx vertical illuminance. Brushed stainless steel luminaire with high degree of protection. Suitable for use in food industry or food processing plants with high demands on product hygiene.

**Technical data**

Material:	stainless steel	Apparent power:	4,4 VA
Illuminant:	1 x 1,8W LED-module	Effective power:	3,6 W
Nominal voltage AC:	230V ±10% 50/60 Hz	Inrush current:	8 A / 50 µs
Nominal voltage DC:	176 - 264 V	Protection class:	I
Nominal current AC:	19 mA	Input terminals:	2.5mm ² feed through wiring
Nominal current DC:	16 mA	Temperature ta:	-15...+40 °C



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

[m]	5.0	6.0	14.6	4.8	1.9
5.0	6.0	14.6	4.8	1.9	
6.0	6.2	15.8	4.9	2.1	
7.0	6.3	16.8	5.3	2.2	
8.0	5.8	17.5	5.7	2.3	
9.0	5.4	17.9	6.0	2.3	
10.0	4.9	17.7	6.3	2.1	
11.0	4.0	16.9	6.5	1.6	

Articles**SN 804.2 W -06 AHB LED J/SV**

Colors	stainless steel	RAL 9016	HWf (special)	RAL (special)
Art. no.	104516385	104519217	104518712	104518813

wall bracket mounting Light colour: 4000 K

Protection category:
IP65