




Robust LED safety luminaire with optimised light distribution for the illumination of areas with high mounting heights. Brushed stainless steel luminaire with high degree of protection. Suitable for use in food industry or food processing plants with high demands on product hygiene.



Technical data

Material:	stainless steel	Effective power:	4,6 W
Illuminant:	1 x 3,5W LED-module	Protection class:	III
Luminous flux:	491 lm	Input terminals:	2.5mm ² feed through wiring
Nominal voltage DC:	24 V ±25 %	Temperature ta:	-15...+40 °C
Nominal current DC:	190 mA		



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

5.5	6.4	15.9
6.0	6.6	16.5
6.5	6.7	17.1
7.0	6.7	17.6
7.5	6.7	18.0
8.0	6.5	18.3
8.5	6.3	18.6
9.0	5.9	18.8
9.5	5.4	19.0
10.0	4.8	19.0

Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8

5.5	4.7	12.9
6.0	4.9	13.6
6.5	4.9	13.7
7.0	4.9	14.7
7.5	4.8	15.4
8.0	4.8	15.8
8.5	4.7	15.9
9.0	4.6	16.2
9.5	4.5	16.6
10.0	4.2	17.0

Articles

SN 804.2 W -12 SHB LED 24V					Name	Accessories	Art. no.
Colors	stainless steel	RAL 9016	HWF (special)	RAL (special)	ILD 24/4-CC-320-C	spare part	101425321
Art. no.	101876167	101876369	101876268	101876470			

wall bracket mounting Light colour: 4000 K Protection category: IP65

