




Robust LED safety luminaire with optimised light distribution for the illumination of areas. Brushed stainless steel luminaire with high degree of protection. Suitable for use in food industry or food processing plants with high demands on product hygiene.



Technical data

Material:	stainless steel
Illuminant:	1 x 3,5W LED-module
Luminous flux:	434 lm
Nominal voltage AC:	230V ±10% 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	25 mA
Nominal current DC:	25 mA

Apparent power:	5,8 VA
Effective power:	5,5 W
Inrush current:	6 A / 22 µs
Protection class:	I
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

2.5	5.3	13.4	
3.0	5.4	14.2	
3.5	5.5	15.0	
4.0	5.5	15.1	
4.5	5.4	15.5	
5.0	5.0	15.5	

Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8

2.5	4.4	11.8	
3.0	4.5	13.0	
3.5	4.4	13.9	
4.0	4.3	14.4	
4.5	3.8	14.9	
5.0	3.4	15.3	

Articles

SN 804.2 W -12 SLB FLD 230V				
Colors	stainless steel	RAL 9016	HWF (special)	RAL (special)
Art. no.	102248003	104517496	102269019	104517500

Name	Accessories	Art. no.
FLD 230/8 – CC – 320 – C	spare part	100903238

wall bracket mounting Light colour: 4000 K Protection category: IP65

