




Robust LED safety luminaire with optimised light distribution for the illumination of areas. Brushed stainless steel luminaire with high degree of protection. Suitable for use in food industry or food processing plants with high demands on product hygiene.



### Technical data

<b>Material:</b>	stainless steel	<b>Effective power:</b>	4,6 W
<b>Illuminant:</b>	1 x 3,5W LED-module	<b>Protection class:</b>	III
<b>Luminous flux:</b>	434 lm	<b>Input terminals:</b>	2.5mm <sup>2</sup> feed through wiring
<b>Nominal voltage DC:</b>	24 V ±25 %	<b>Temperature ta:</b>	-15...+40 °C
<b>Nominal current DC:</b>	190 mA		



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

2.5	5.3	13.4
3.0	5.4	14.2
3.5	5.5	15.0
4.0	5.5	15.1
4.5	5.4	15.5
5.0	5.0	15.5

Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8

2.5	4.4	11.8
3.0	4.5	13.0
3.5	4.4	13.9
4.0	4.3	14.4
4.5	3.8	14.9
5.0	3.4	15.3

### Articles

SN 804.2 W -12 SLB LED 24V					Name	Accessories	Art. no.
Colors	stainless steel	RAL 9016	HWF (special)	RAL (special)	ILD 24/4-CC-320-C	spare part	101425321
Art. no.	102247902	104516486	104487285	104516587			

wall bracket mounting      Light colour: 4000 K      Protection category: IP65

