




Robust LED safety luminaire with optimised light distribution for the illumination of areas. Brushed stainless steel luminaire with high degree of protection. Suitable for use in food industry or food processing plants with high demands on product hygiene.



### Technical data

<b>Material:</b>	stainless steel	<b>Apparent power:</b>	7,6 VA
<b>Illuminant:</b>	1 x 3,5W LED-module	<b>Effective power:</b>	5,7 W
<b>Luminous flux:</b>	434 lm	<b>Inrush current:</b>	8 A / 50 µs
<b>Nominal voltage AC:</b>	230V ±10% 50/60 Hz	<b>Protection class:</b>	I
<b>Nominal voltage DC:</b>	176 - 264 V	<b>Input terminals:</b>	2.5mm <sup>2</sup> feed through wiring
<b>Nominal current AC:</b>	33 mA	<b>Temperature ta:</b>	-15...+40 °C
<b>Nominal current DC:</b>	25 mA		



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

Distance (m)	2.5	5.3	13.4
2.5	3.0	5.4	14.2
3.5	5.5	15.0	
4.0	5.5	15.1	
4.5	5.4	15.5	
5.0	5.0	15.5	

Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8

Distance (m)	2.5	4.4	11.8
3.0	4.5	13.0	
3.5	4.4	13.9	
4.0	4.3	14.4	
4.5	3.8	14.9	
5.0	3.4	15.3	

### Articles

SN 804.2 W -12 SLB LED J/SV					Name	Accessories	Art. no.
Colors	stainless steel	RAL 9016	HWF (special)	RAL (special)	J-ET 9/24 SVmax.24VDC,320mAconst	spare part	101420267
Art. no.	102399866	104519015	104518308	104175976			

wall bracket mounting      Light colour: 4000 K      Protection category: IP65

