

230V**SN 8040-41 Downlights**

For connection to FUSION central battery- or emergency power (NEA) systems




Elegant high-quality LED downlight ideal for area or escape route illumination. Powder-coated aluminium housing for ceiling mounting with high protection category and without any visible screws.

Technical data

Material:	aluminium powder-coated
Illuminant:	4 x 1W LED-module
Luminous flux:	310 lm
Nominal voltage AC:	230V ±10% 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	27 mA
Nominal current DC:	28 mA

Apparent power:	6,3 VA
Effective power:	6,0 W
Inrush current:	6 A / 22 µs
Protection class:	I
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

[m]	[m]	[m]
2.5	3.7	8.5
3.0	4.1	9.7
4.0	4.7	11.5
5.0	5.0	12.9
6.0	5.1	13.9
7.0	4.9	14.3
8.0	4.5	14.4
9.0	3.7	14.3
10.0	2.5	13.8

Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8

[m]	[m]	[m]
2.5	2.7	6.4
3.0	3.1	7.3
4.0	3.6	9.0
5.0	3.7	10.6
6.0	3.7	11.8
7.0	3.6	12.4
8.0	3.4	12.8
9.0	3.1	12.6
10.0	2.6	12.4

Articles

SN 8040 -41 FLD 230V			
Colors	RAL 7015	RAL 9016	RAL (special)
Art. no.	101370757	101370656	101370858

Name	Accessories	Art. no.
FLD 230/8 – CC – 320 – C	Ersatzteil	100903238

ceiling mounting Light colour: 6500 K Protection category: IP65

