




Elegant high-quality LED downlight ideal for area or escape route illumination. Powder-coated aluminium housing for ceiling mounting with high protection category and without any visible screws.

Technical data

Material:	aluminium powder-coated	Nominal current DC:	200 mA
Illuminant:	4 x 1W LED-module	Protection class:	I
Luminous flux:	310 lm	Input terminals:	2.5mm ² feed through wiring
Nominal voltage DC:	24 V ±25 %	Temperature ta:	-15...+40 °C



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

Beam diameter [m]	2.5	3.7	8.5
2.5	3.7	4.1	9.7
3.0	4.0	4.7	11.5
4.0	5.0	5.1	13.9
5.0	4.9	4.5	14.4
6.0	3.7	3.7	14.3
7.0	2.5	2.5	13.8
8.0	2.5	2.5	13.8
9.0	2.5	2.5	13.8
10.0	2.5	2.5	13.8

Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8

Beam diameter [m]	2.5	2.7	6.4
2.5	3.1	3.6	9.0
3.0	3.1	3.6	9.0
4.0	3.6	3.7	11.8
5.0	3.7	3.6	12.4
6.0	3.7	3.4	12.8
7.0	3.6	3.1	12.6
8.0	3.4	2.6	12.4
9.0	3.1	2.6	12.4
10.0	2.6	2.6	12.4

Articles

SN 8040-41 LED 24V

Colors	RAL 7015	RAL 9016	HWF (special)	RAL (special)
Art. no.	101354185	101354084	101353983	101354286
ceiling mounting	Light colour: 6500 K		Protection category: IP65	

