

**230V****SN 8040-41 Downlights****J/SV**

For connection to JOKER-central battery systems




Elegant high-quality LED downlight ideal for area or escape route illumination. Powder-coated aluminium housing for ceiling mounting with high protection category and without any visible screws.

**Technical data**

<b>Material:</b>	aluminium powder-coated
<b>Illuminant:</b>	4 x 1W LED-module
<b>Luminous flux:</b>	310 lm
<b>Nominal voltage AC:</b>	230V ±10% 50/60 Hz
<b>Nominal voltage DC:</b>	176 - 264 V
<b>Nominal current AC:</b>	36 mA
<b>Nominal current DC:</b>	32 mA

<b>Apparent power:</b>	8,3 VA
<b>Effective power:</b>	7,4 W
<b>Inrush current:</b>	8 A / 50 µs
<b>Protection class:</b>	I
<b>Input terminals:</b>	2.5mm <sup>2</sup> feed through wiring
<b>Temperature ta:</b>	-15...+40 °C



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

Beam diameter [m]	Beam diameter [m]	Beam diameter [m]
2.5	3.7	8.5
3.0	4.1	9.7
4.0	4.7	11.5
5.0	5.0	12.9
6.0	5.1	13.9
7.0	4.9	14.3
8.0	4.5	14.4
9.0	3.7	14.3
10.0	2.5	13.8

Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8

Beam diameter [m]	Beam diameter [m]	Beam diameter [m]
2.5	2.7	6.4
3.0	3.1	7.3
4.0	3.6	9.0
5.0	3.7	10.6
6.0	3.7	11.8
7.0	3.6	12.4
8.0	3.4	12.8
9.0	3.1	12.6
10.0	2.6	12.4

**Articles**

SN 8040 -41 LED J/SV				
Colors	RAL 7015	RAL 9016	HWf (special)	RAL (special)
Art. no.	101293460	101293359	101293258	101293561

ceiling mounting      Light colour: 6500 K      Protection category: IP65

Name	Accessories	Art. no.
4 REBEL 100LM KWS 39X39 GB-M3mit 4x100 lm LEDs,	Ersatzteil	091256
J - ET 9 / 24 SV -max.24VDC,320mAconst	Ersatzteil	101420267
LED replacement kit SN 8040-41, RAL 9016	Ersatzteil	101174838

