

230V**SN 8040-41 Downlights****NE/SV**

For connection to INOTEC-NEA-monitoring systems




Elegant high-quality LED downlight ideal for area or escape route illumination. Powder-coated aluminium housing for ceiling mounting with high protection category and without any visible screws.

Technical data

Material:	aluminium powder-coated
Illuminant:	4 x 1W LED-module
Luminous flux:	310 lm
Nominal voltage AC:	230V AC ±10% 50/60 Hz
Nominal current AC:	36 mA
Apparent power:	8,3 VA

Effective power:	7,4 W
Inrush current:	8 A / 50 µs
Protection class:	I
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

[m]	2.5	3.7	8.5
2.5	3.7	4.1	9.7
3.0	4.1	4.7	11.5
4.0	4.7	5.0	12.9
5.0	5.0	5.1	13.9
6.0	5.1	4.9	14.3
7.0	4.9	4.5	14.4
8.0	4.5	3.7	14.3
9.0	3.7	2.5	13.8
10.0	2.5		

Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8

[m]	2.5	2.7	6.4
2.5	2.7	3.1	7.3
3.0	3.1	3.6	9.0
4.0	3.6	3.7	10.6
5.0	3.7	3.4	12.8
6.0	3.7	3.1	12.6
7.0	3.6	2.6	12.4
8.0	3.4		
9.0	3.1		
10.0	2.6		

Articles

SN 8040 -41 LED NE/SV		
Colors	RAL 9016	RAL (special)
Art. no.	101293965	101294066
ceiling mounting	Light colour: 6500 K	Protection category: IP65

Name	Accessories	Art. no.
4 REBEL 100LM KWS 39X39 GB-M3mit 4x100 lm LEDs,	Ersatzteil	091256
LED replacement kit SN 8040-41, RAL 9016	Ersatzteil	101174838
NE - ET 9 / 24 SV -max.24VDC,320mAconst	Ersatzteil	101420570

