




Elegant high-quality LED downlight ideal for area or escape route illumination. Perfect for combined usage of safety and general lighting. Possible adaption to the light colour of the general lighting by Translucent-Emitting-Surface (TES) technology. Powder-coated aluminium housing for ceiling mounting with high protection category and without any visible screws.

Technical data

| | | | |
|----------------------------|-------------------------|----------------------------|--|
| Material: | Aluminium powder-coated | Nominal current DC: | 200 mA |
| Illuminant: | 4 x 1W LED-module | Protection class: | I |
| Luminous flux: | 261 lm | Input terminals: | 2.5mm ² feed through wiring |
| Nominal voltage DC: | 24 V ±25 % | Temperature ta: | -15...+40 °C |



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

| Height [m] | Beam diameter [m] | Beam diameter [m] |
|------------|-------------------|-------------------|
| 2.5 | 3.7 | 9.4 |
| 3.0 | 3.8 | 10.1 |
| 4.0 | 4.1 | 11.0 |
| 5.0 | 4.1 | 11.6 |
| 6.0 | 3.8 | 11.7 |

Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8

| Height [m] | Beam diameter [m] | Beam diameter [m] |
|------------|-------------------|-------------------|
| 2.5 | 2.5 | 8.0 |
| 3.0 | 2.7 | 8.6 |
| 4.0 | 2.7 | 9.8 |
| 5.0 | 2.7 | 10.6 |
| 6.0 | 2.7 | 10.6 |

Available colours Add colour code to the article no. e.g. 800 014 **LXX**


RAL 7015 (Slate grey): **L16** ■ RAL 9016 (Traffic white): **L04** □ Special colour: **L99** 🌈

Articles

SN 8040 LED 24V

Art. no. 810 307


Ceiling mounting Light colour: 2700 K Protection category: IP65



SN 8040 LED 24V

Art. no. 810 308

Ceiling mounting Light colour: 3500 K Protection category: IP65



SN 8040 LED 24V

Art. no. 810 309

Ceiling mounting Light colour: 4300 K Protection category: IP65

