




Elegant high-quality LED downlight ideal for area or escape route illumination. Perfect for combined usage of safety and general lighting. Possible adaption to the light colour of the general lighting by Translucent-Emitting-Surface (TES) technology. Powder-coated aluminium housing for ceiling mounting with high protection category and without any visible screws.

**Technical data**

<b>Material:</b>	Aluminium powder-coated
<b>Illuminant:</b>	4 x 1W LED-module
<b>Luminous flux:</b>	261 lm
<b>Nominal voltage AC:</b>	230V AC ±10% 50/60 Hz
<b>Nominal current AC:</b>	36 mA

<b>Apparent power:</b>	8,3 VA
<b>Inrush current:</b>	8 A / 50 µs
<b>Protection class:</b>	I
<b>Input terminals:</b>	2.5mm <sup>2</sup> feed through wiring
<b>Temperature ta:</b>	-15...+40 °C



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

2.5	3.7	9.4
3.0	3.8	10.1
4.0	4.1	11.0
5.0	4.1	11.6
6.0	3.8	11.7

Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8

2.5	2.5	8.0
3.0	2.7	8.6
4.0	2.7	9.8
5.0	2.7	10.6
6.0	2.7	10.6


**Available colours** Add colour code to the article no. e.g. 800 014 **LXX**

RAL 7015 (Slate grey): **L16** ■ RAL 9016 (Traffic white): **L04** □ Special colour: **L99** 🌈

**Articles**


**SN 8040 LED NE/SV** Art. no. 808 164

Ceiling mounting Light colour: 2700 K Protection category: IP65



**SN 8040 LED NE/SV** Art. no. 808 167

Ceiling mounting Light colour: 3500 K Protection category: IP65



**SN 8040 LED NE/SV** Art. no. 808 170

Ceiling mounting Light colour: 4300 K Protection category: IP65

