




LED safety luminaire with optimised light distribution for the illumination of areas. Geräteträger für Maxos fusion und Maxos unify (LL5..T 4x2.5+8x1.5 Gen2 ..) Tragschiene. Einfaches Einclippen mit Hilfe der werkzeuglos zu betätigenden Rastverschlüsse zur elektrischen Kontaktierung inkl. Stromkreiswahl und mechanischen Befestigung.

Incl. 4-chip LED illuminant for maximum safety.

Technical data

Illuminant:	replaceable 1 x 3,5W LED-module	Effective power:	4,6 W
Luminous flux:	517 lm	Input terminals:	2.5mm ² feed through wiring
Nominal voltage DC:	24 V ±25 %	Temperature ta:	-15...+40 °C
Nominal current DC:	190 mA		



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

Beam diameter (m)	Beam area (m²)	Beam diameter (m)
2.5	5.8	15.1
3.0	5.9	16.1
3.5	5.8	16.5
4.0	5.7	16.7
4.5	5.4	16.6
5.0	4.9	16.5
5.5	3.7	16.3
6.0	1.4	15.9

Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8


Beam diameter (m)	Beam area (m²)	Beam diameter (m)
2.5	4.5	12.6
3.0	4.9	14.0
3.5	5.0	14.9
4.0	4.6	15.5
4.5	4.1	15.1
5.0	3.9	14.5
5.5	3.7	14.3
6.0	3.5	14.1

Articles

SN 8300 -12 SLB LED 24V		Name	Accessories	Art. no.
Colors	RAL 9003	ILD 24/4-CC-320-C	spare part	101425321
Art. no.	104319456			

for installation in Signify
Maxos fusion & Maxos unify
trunking rail 13 -cores

Light colour: 4000 K






LED safety luminaire with optimised light distribution for the illumination of areas. Geräteträger für Maxos fusion und Maxos unify (LL5..T 4x2.5+8x1.5 Gen2 ..) Tragschiene. Einfaches Einclippen mit Hilfe der werkzeuglos zu betätigenden Rastverschlüsse zur elektrischen Kontaktierung inkl. Stromkreiswahl und mechanischen Befestigung.

Incl. 4-chip LED illuminant for maximum safety.

Technical data

Illuminant:	replaceable 1 x 3,5W LED-module	Effective power:	4,6 W
Luminous flux:	517 lm	Input terminals:	2.5mm ² feed through wiring
Nominal voltage DC:	24 V ±25 %	Temperature ta:	-15...+40 °C
Nominal current DC:	190 mA		



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

Beam diameter (m)	Beam area (m²)	Beam diameter (m)
2.5	5.8	15.1
3.0	5.9	16.1
3.5	5.8	16.5
4.0	5.7	16.7
4.5	5.4	16.6
5.0	4.9	16.5
5.5	3.7	16.3
6.0	1.4	15.9

Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8

Beam diameter (m)	Beam area (m²)	Beam diameter (m)
2.5	4.5	12.6
3.0	4.9	14.0
3.5	5.0	14.9
4.0	4.6	15.5
4.5	4.1	15.1
5.0	3.9	14.5
5.5	3.7	14.3
6.0	3.5	14.1

Articles

SN 8300 -12 SLB LED 24V		Name	Accessories	Art. no.
Colors	RAL 9003	ILD 24/4-CC-320-C	spare part	101425321
Art. no.	104319456			

for installation in Signify
Maxos fusion & Maxos unify
trunking rail 13 -cores

Light colour: 4000 K

