

230V**SN 8400-03 ALB Downlights****J/SV**

For connection to JOKER-central battery systems




LED safety luminaire with optimised light distribution for the illumination of escape routes. Housing made of powder-coated aluminium for ceiling mounting with optional cable entry at the side. Incl. 4-chip LED illuminant for maximum safety.

**Technical data**

Material:	die-cast aluminum powder-coated
Illuminant:	1 x 0,9W LED-module
Luminous flux:	133 lm
Nominal voltage AC:	230V ±10% 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	15 mA
Nominal current DC:	12 mA

Apparent power:	3,5 VA
Effective power:	2,6 W
Inrush current:	8 A / 50 µs
Protection class:	I
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C




Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

Beam angle (°)	2.5	6.7	16.9	4.7	1.9
100	3.0	5.3	18.1	5.1	2.0
75	3.5	4.9	17.8	5.5	1.8
50	4.0	3.9	16.6	5.6	1.5
25	4.5	3.1	14.4	5.5	1.1

Articles**SN 8400 -03 ALB LED J/SV round**




Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102057437	100777744	101298110

ceiling mounting Light colour: 4000 K Protection category: IP40

**SN 8400 -03 ALB LED J/SV square**

Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102058245	101299625	101299726

ceiling mounting Light colour: 4000 K Protection category: IP40

**Chain suspension SN 8400 rd, RAL 9016 Art. no. 101445529****Cable suspension SN 8400 sq, RAL 9016 Art. no. 101445731**

Subject to technical changes! Due to component tolerances measured values may vary!

www.inotec-licht.de



2023.10.21

Name	Accessories	Art. no.
Cable suspension SN 8400 sq, RAL 9016	optional	101445731
Chain suspension SN 8400 rd, RAL 9016	optional	101445529
J - ET 9 / 24 SV -max.24VDC,320mAconst	Ersatzteil	101420267
LM 39x39 1(3V)/4K KB150	Ersatzteil	104556502