




LED safety luminaire with optimised light distribution for the illumination of escape routes. Housing made of powder-coated aluminium for ceiling mounting with optional cable entry at the side. Incl. 4-chip LED illuminant for maximum safety.



Technical data

Material:	die-cast aluminum powder-coated
Illuminant:	1 x 0,9W LED-module
Luminous flux:	133 lm
Nominal voltage AC:	230V ±10% 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	15 mA
Nominal current DC:	12 mA

Apparent power:	3,5 VA
Effective power:	2,6 W
Inrush current:	8 A / 50 µs
Protection class:	I
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

2.5	6.7	16.9	4.7	1.9
3.0	5.3	18.1	5.1	2.0
3.5	4.9	17.8	5.5	1.8
4.0	3.9	16.6	5.6	1.5
4.5	3.1	14.4	5.5	1.1

Articles

SN 8400 -03 ALB LED J/SV round



Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102057437	100777744	101298110

ceiling mounting Light colour: 4000 K Protection category: IP40

SN 8400 -03 ALB LED J/SV square

Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102058245	101299625	101299726

ceiling mounting Light colour: 4000 K Protection category: IP40





Chain suspension SN 8400 rd, RAL 9016

Art. no. 101445529

Cable suspension SN 8400 sq, RAL 9016

Art. no. 101445731



Name	Accessories	Art. no.
Cable suspension SN 8400 sq, RAL 9016	optional	101445731
Chain suspension SN 8400 rd, RAL 9016	optional	101445529
J-ET 9/24 SVmax.24VDC,320mAconst	spare part	101420267
LM 39x39 1(3V)/4K KB150 230V LED Modul	spare part	104556502