




LED safety luminaire with optimised light distribution for the illumination of escape routes. Housing made of powder-coated aluminium for ceiling mounting with optional cable entry at the side. Incl. 4-chip LED illuminant for maximum safety.



**Technical data**

<b>Material:</b>	die-cast aluminum powder-coated
<b>Illuminant:</b>	1 x 0,9W LED-module
<b>Luminous flux:</b>	133 lm
<b>Nominal voltage AC:</b>	230V AC ±10% 50/60 Hz
<b>Nominal current AC:</b>	15 mA
<b>Apparent power:</b>	3,5 VA

<b>Effective power:</b>	2,6 W
<b>Inrush current:</b>	8 A / 50 µs
<b>Protection class:</b>	I
<b>Input terminals:</b>	2.5mm <sup>2</sup> feed through wiring
<b>Temperature ta:</b>	-15...+40 °C





Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

[m]	2.5	6.7	16.9	4.7	1.9
2.5	6.7	16.9	4.7	1.9	
3.0	5.3	18.1	5.1	2.0	
3.5	4.9	17.8	5.5	1.8	
4.0	3.9	16.6	5.6	1.5	
4.5	3.1	14.4	5.5	1.1	

**Articles**



SN 8400 -03 ALB LED NE/SV round			
Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102057841	101298817	101298918
ceiling mounting	Light colour: 4000 K		Protection category: IP40

SN 8400 -03 ALB LED NE/SV square			
Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102058649	101300433	101300534
ceiling mounting	Light colour: 4000 K		Protection category: IP40



**Chain suspension SN 8400 rd, RAL 9016** Art. no. 101445529

**Cable suspension SN 8400 sq, RAL 9016** Art. no. 101445731



<b>Name</b>	<b>Accessories</b>	<b>Art. no.</b>
Cable suspension SN 8400 sq, RAL 9016	optional	101445731
Chain suspension SN 8400 rd, RAL 9016	optional	101445529
LM 39x39 1(3V)/4K KB150 230V LED Modul	spare part	104556502
NE-ET 9/24 SVmax.24VDC,320mAconst	spare part	101420570