

**230V****SN 8400-03 ALB Downlights****NE/SV**

For connection to INOTEC-NEA-monitoring systems




LED safety luminaire with optimised light distribution for the illumination of escape routes. Housing made of powder-coated aluminium for ceiling mounting with optional cable entry at the side. Incl. 4-chip LED illuminant for maximum safety.

**Technical data**

<b>Material:</b>	die-cast aluminum powder-coated
<b>Illuminant:</b>	1 x 0,9W LED-module
<b>Luminous flux:</b>	133 lm
<b>Nominal voltage AC:</b>	230V AC ±10% 50/60 Hz
<b>Nominal current AC:</b>	15 mA
<b>Apparent power:</b>	3,5 VA

<b>Effective power:</b>	2,6 W
<b>Inrush current:</b>	8 A / 50 µs
<b>Protection class:</b>	I
<b>Input terminals:</b>	2.5mm <sup>2</sup> feed through wiring
<b>Temperature ta:</b>	-15...+40 °C




Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

[m]	⊘	⊘	⊘	⊘
2.5	6.7	16.9	4.7	1.9
3.0	5.3	18.1	5.1	2.0
3.5	4.9	17.8	5.5	1.8
4.0	3.9	16.6	5.6	1.5
4.5	3.1	14.4	5.5	1.1

**Articles****SN 8400 -03 ALB LED NE/SV round**


Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102057841	101298817	101298918

ceiling mounting      Light colour: 4000 K      Protection category: IP40


**SN 8400 -03 ALB LED NE/SV square**

Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102058649	101300433	101300534


ceiling mounting      Light colour: 4000 K      Protection category: IP40



**Chain suspension SN 8400 rd, RAL 9016**      Art. no. 101445529



**Cable suspension SN 8400 sq, RAL 9016**      Art. no. 101445731



<b>Name</b>	<b>Accessories</b>	<b>Art. no.</b>
Cable suspension SN 8400 sq, RAL 9016	optional	101445731
Chain suspension SN 8400 rd, RAL 9016	optional	101445529
LM 39x39 1(3V)/4K KB150	Ersatzteil	104556502
NE - ET 9 / 24 SV -max.24VDC,320mAconst	Ersatzteil	101420570