

230V SN 8400-03 SLB Downlights

FLD For connection to FUSION central battery- or emergency power (NEA) systems




LED safety luminaire with optimised light distribution for the illumination of small areas such as lavatories or electrical operating rooms with a luminaire. Housing made of powder-coated aluminium for ceiling mounting with optional cable entry at the side. Incl. 4-chip LED illuminant for maximum safety.



Technical data

Material:	die-cast aluminum powder-coated
Illuminant:	1 x 0,9W LED-module
Luminous flux:	145 lm
Nominal voltage AC:	230V ±10% 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	13 mA
Nominal current DC:	12 mA

Apparent power:	3,0 VA
Effective power:	2,6 W
Inrush current:	6 A / 22 µs
Protection class:	I
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

Distance [m]	1.0lx	0.5lx
2.5	3.3	8.2
3.0	3.5	8.8
3.5	3.5	9.3
4.0	3.4	9.7
4.5	3.1	9.9
5.0	2.6	10.0

Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8


Distance [m]	1.0lx	0.5lx
2.5	2.2	6.8
3.0	2.3	7.4
3.5	2.5	8.0
4.0	2.6	8.4
4.5	2.5	8.6
5.0	2.4	8.2

Articles


SN 8400 -03 SLB FLD 230V round

Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102066531	101388844	101388945

ceiling mounting Light colour: 4000 K Protection category: IP40




Chain suspension SN 8400 rd, RAL 9016 Art. no. 101445529




SN 8400 -03 SLB FLD 230V square

Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102066733	101389248	101389349

ceiling mounting Light colour: 4000 K Protection category: IP40



Cable suspension SN 8400 sq, RAL 9016 Art. no. 101445731



Name	Accessories	Art. no.
Cable suspension SN 8400 sq, RAL 9016	optional	101445731
Chain suspension SN 8400 rd, RAL 9016	optional	101445529
FLD 230/8 – CC – 320 – C	Ersatzteil	100903238
LM 39x39 1(3V)/4K KB150	Ersatzteil	104556502