




LED safety luminaire with optimised light distribution for the illumination of small areas such as lavatories or electrical operating rooms with a luminaire. Housing made of powder-coated aluminium for ceiling mounting with optional cable entry at the side. Incl. 4-chip LED illuminant for maximum safety.



Technical data

| | |
|----------------------------|---------------------------------|
| Material: | die-cast aluminum powder-coated |
| Illuminant: | 1 x 0,9W LED-module |
| Luminous flux: | 145 lm |
| Nominal voltage AC: | 230V ±10% 50/60 Hz |
| Nominal voltage DC: | 176 - 264 V |
| Nominal current AC: | 13 mA |
| Nominal current DC: | 12 mA |

| | |
|--------------------------|--|
| Apparent power: | 3,0 VA |
| Effective power: | 2,6 W |
| Inrush current: | 6 A / 22 µs |
| Protection class: | I |
| Input terminals: | 2.5mm ² feed through wiring |
| Temperature ta: | -15...+40 °C |



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

| Distance [m] | 2.5 | 3.3 | 8.2 |
|--------------|-----|------|-----|
| 2.5 | 3.0 | 3.5 | 8.8 |
| 3.5 | 3.5 | 9.3 | |
| 4.0 | 3.4 | 9.7 | |
| 4.5 | 3.1 | 9.9 | |
| 5.0 | 2.6 | 10.0 | |

Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8

| Distance [m] | 2.5 | 2.2 | 6.8 |
|--------------|-----|-----|-----|
| 2.5 | 3.0 | 2.3 | 7.4 |
| 3.5 | 3.5 | 2.5 | 8.0 |
| 4.0 | 3.4 | 2.6 | 8.4 |
| 4.5 | 3.1 | 2.5 | 8.6 |
| 5.0 | 2.4 | 2.4 | 8.2 |

Articles

SN 8400 -03 SLB FLD 230V round



| Colors | RAL 9005 | RAL 9016 | RAL (special) |
|----------|-----------|-----------|---------------|
| Art. no. | 102066531 | 101388844 | 101388945 |

ceiling mounting Light colour: 4000 K Protection category: IP40

SN 8400 -03 SLB FLD 230V square



| Colors | RAL 9005 | RAL 9016 | RAL (special) |
|----------|-----------|-----------|---------------|
| Art. no. | 102066733 | 101389248 | 101389349 |

ceiling mounting Light colour: 4000 K Protection category: IP40



Chain suspension SN 8400 rd, RAL 9016 Art. no. 101445529

Cable suspension SN 8400 sq, RAL 9016 Art. no. 101445731



| Name | Accessories | Art. no. |
|--|--------------------|-----------------|
| Cable suspension SN 8400 sq, RAL 9016 | optional | 101445731 |
| Chain suspension SN 8400 rd, RAL 9016 | optional | 101445529 |
| FLD 230/8 – CC – 320 – C | spare part | 100903238 |
| LM 39x39 1(3V)/4K KB150 230V LED Modul | spare part | 104556502 |