




LED safety luminaire with optimised light distribution for the illumination of small areas such as lavatories or electrical operating rooms with a luminaire. Housing made of powder-coated aluminium for ceiling mounting with optional cable entry at the side. Incl. 4-chip LED illuminant for maximum safety.



Technical data

Material:	die-cast aluminum powder-coated
Illuminant:	1 x 0,9W LED-module
Luminous flux:	145 lm
Nominal voltage AC:	230V AC ±10% 50/60 Hz
Nominal current AC:	15 mA
Apparent power:	3,5 VA

Effective power:	2,6 W
Inrush current:	8 A / 50 µs
Protection class:	I
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

Beam diameter [m]	2.5	3.3	8.2
2.5	3.0	3.5	8.8
3.0	3.5	9.3	
3.5	4.0	9.7	
4.0	4.5	9.9	
4.5	5.0	10.0	



Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8

Beam diameter [m]	2.5	2.2	6.8
2.5	3.0	2.3	7.4
3.0	3.5	2.5	8.0
3.5	4.0	2.6	8.4
4.0	4.5	2.5	8.6
4.5	5.0	2.4	8.2

Articles



SN 8400 -03 SLB LED NE/SV round			
Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102059053	101301241	101301342
ceiling mounting	Light colour: 4000 K		Protection category: IP40

SN 8400 -03 SLB LED NE/SV square			
Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102059457	101302049	101302150
ceiling mounting	Light colour: 4000 K		Protection category: IP40



Chain suspension SN 8400 rd, RAL 9016 Art. no. 101445529

Cable suspension SN 8400 sq, RAL 9016 Art. no. 101445731



Name	Accessories	Art. no.
Cable suspension SN 8400 sq, RAL 9016	optional	101445731
Chain suspension SN 8400 rd, RAL 9016	optional	101445529
LM 39x39 1(3V)/4K KB150 230V LED Modul	spare part	104556502
NE-ET 9/24 SVmax.24VDC,320mAconst	spare part	101420570