




LED safety luminaire with optimised light distribution for the illumination of escape routes with high mounting heights. Also suitable for illumination of firefighting and fire alarm systems as well as first aid stations with 5 lx vertical illuminance. Housing made of powder-coated aluminium for ceiling mounting with optional cable entry at the side. Incl. 4-chip LED illuminant for maximum safety.



Technical data

Material:	die-cast aluminum powder-coated
Illuminant:	1 x 1,8W LED-module
Luminous flux:	275 lm
Nominal voltage AC:	230V ±10% 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	19 mA
Nominal current DC:	16 mA

Apparent power:	4,4 VA
Effective power:	3,6 W
Inrush current:	8 A / 50 µs
Protection class:	I
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8


Mounting height (m)	1.0m	1.5m	2.0m	2.5m	3.0m
5.0	6.6	16.0	5.0	1.9	
6.0	7.2	17.4	4.9	2.1	
7.0	7.5	18.7	5.4	2.3	
8.0	7.4	19.9	5.7	2.4	
9.0	6.6	20.7	6.2	2.4	
10.0	5.9	21.1	6.5	2.3	
11.0	4.9	20.9	6.7	2.1	

Articles

SN 8400 -06 AHB LED J/SV round

Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102057538	101298211	101298312


ceiling mounting Light colour: 4000 K Protection category: IP40




SN 8400 -06 AHB LED J/SV square

Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102058346	101299827	101299928


ceiling mounting Light colour: 4000 K Protection category: IP40



Chain suspension SN 8400 rd, RAL 9016 Art. no. 101445529



Cable suspension SN 8400 sq, RAL 9016 Art. no. 101445731



Name	Accessories	Art. no.
Cable suspension SN 8400 sq, RAL 9016	optional	101445731
Chain suspension SN 8400 rd, RAL 9016	optional	101445529
J-ET 9/24 SVmax.24VDC,320mAconst	spare part	101420267
LM 39x39 1(6V)/4K KB150 LED Modul	spare part	104556704