




LED safety luminaire with optimised light distribution for the illumination of escape routes with high mounting heights. Also suitable for illumination of firefighting and fire alarm systems as well as first aid stations with 5 lx vertical illuminance. Housing made of powder-coated aluminium for ceiling mounting with optional cable entry at the side. Incl. 4-chip LED illuminant for maximum safety.



Technical data

Material:	die-cast aluminum powder-coated
Illuminant:	1 x 1,8W LED-module
Luminous flux:	275 lm
Nominal voltage AC:	230V AC ±10% 50/60 Hz
Nominal current AC:	19 mA
Apparent power:	4,4 VA

Effective power:	3,6 W
Inrush current:	8 A / 50 µs
Protection class:	I
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C





Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

Height (m)	1.0lx	1.5lx	2.0lx	3.0lx	4.0lx
5.0	6.6	16.0	5.0	1.9	
6.0	7.2	17.4	4.9	2.1	
7.0	7.5	18.7	5.4	2.3	
8.0	7.4	19.9	5.7	2.4	
9.0	6.6	20.7	6.2	2.4	
10.0	5.9	21.1	6.5	2.3	
11.0	4.9	20.9	6.7	2.1	

Articles



SN 8400 -06 AHB LED NE/SV round			
Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102057942	101299019	101299120
ceiling mounting	Light colour: 4000 K		Protection category: IP40

SN 8400 -06 AHB LED NE/SV square			
Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102058750	101300635	101300736
ceiling mounting	Light colour: 4000 K		Protection category: IP40



Chain suspension SN 8400 rd, RAL 9016 Art. no. 101445529

Cable suspension SN 8400 sq, RAL 9016 Art. no. 101445731



Name	Accessories	Art. no.
Cable suspension SN 8400 sq, RAL 9016	optional	101445731
Chain suspension SN 8400 rd, RAL 9016	optional	101445529
LM 39x39 1(6V)/4K KB150 LED Modul	spare part	104556704
NE-ET 9/24 SVmax.24VDC,320mAconst	spare part	101420570