


230V**SN 8400-12 SHB Downlights****NE/SV**

For connection to INOTEC-NEA-monitoring systems




LED safety luminaire with optimised light distribution for the illumination of areas with high mounting heights. Housing made of powder-coated aluminium for ceiling mounting with optional cable entry at the side. Incl. 4-chip LED illuminant for maximum safety.

**Technical data**

Material:	die-cast aluminum powder-coated
Illuminant:	1 x 3,5W LED-module
Luminous flux:	543 lm
Nominal voltage AC:	230V AC ±10% 50/60 Hz
Nominal current AC:	33 mA
Apparent power:	7,6 VA

Effective power:	5,7 W
Inrush current:	8 A / 50 µs
Protection class:	I
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

Height [m]	1.0lx	0.8lx
6.0	6.9	17.3
6.5	7.0	17.9
7.0	7.0	18.3
7.5	6.9	18.8
8.0	6.8	19.1
8.5	6.5	19.4
9.0	6.2	19.6
9.5	5.7	19.7
10.0	5.0	19.8


Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8

Height [m]	1.0lx	0.8lx
6.0	4.9	14.2
6.5	5.1	14.7
7.0	5.0	14.9
7.5	4.9	16.2
8.0	4.7	16.3
8.5	4.7	16.8
9.0	4.6	17.5
9.5	4.5	17.7
10.0	4.3	16.6

Articles**SN 8400 -12 SHB LED NE/SV round**




Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102057740	101298615	101298716

ceiling mounting Light colour: 4000 K Protection category: IP40

**SN 8400 -12 SHB LED NE/SV square**

Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102058548	101300231	101300332

ceiling mounting Light colour: 4000 K Protection category: IP40

**Chain suspension SN 8400 rd, RAL 9016 Art. no. 101445529****Cable suspension SN 8400 sq, RAL 9016 Art. no. 101445731**

Name	Accessories	Art. no.
Cable suspension SN 8400 sq, RAL 9016	optional	101445731
Chain suspension SN 8400 rd, RAL 9016	optional	101445529
LM 39x39 1(12V)/4K KB150	Ersatzteil	104556401
NE - ET 9 / 24 SV -max.24VDC,320mAconst	Ersatzteil	101420570