

230V**SN 8400-12 SLB Downlights****J/SV**

For connection to JOKER-central battery systems




LED safety luminaire with optimised light distribution for the illumination of areas. Housing made of powder-coated aluminium for ceiling mounting with optional cable entry at the side. Incl. 4-chip LED illuminant for maximum safety.

**Technical data**

Material:	die-cast aluminum powder-coated
Illuminant:	1 x 3,5W LED-module
Luminous flux:	513 lm
Nominal voltage AC:	230V ±10% 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	33 mA
Nominal current DC:	25 mA

Apparent power:	7,6 VA
Effective power:	5,7 W
Inrush current:	8 A / 50 µs
Protection class:	I
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

Distance [m]	Beam diameter [m]	Beam diameter [m]
2.5	6.2	16.0
3.0	6.3	17.0
3.5	6.1	17.6
4.0	5.7	17.8
4.5	5.3	17.7
5.0	4.7	17.3
5.5	3.5	16.4
6.0	1.4	15.6


Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8

Distance [m]	Beam diameter [m]	Beam diameter [m]
2.5	4.5	12.6
3.0	4.9	14.0
3.5	5.0	14.9
4.0	4.6	15.5
4.5	4.1	15.1
5.0	3.9	14.5
5.5	3.7	14.3
6.0	3.5	14.1


Articles**SN 8400 -12 SLB LED J/SV round**

Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102057235	100777138	100777340

ceiling mounting Light colour: 4000 K Protection category: IP40




Chain suspension SN 8400 rd, RAL 9016 Art. no. 101445529


**SN 8400 -12 SLB LED J/SV square**

Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102058043	101299221	101299322

ceiling mounting Light colour: 4000 K Protection category: IP40



Cable suspension SN 8400 sq, RAL 9016 Art. no. 101445731



Subject to technical changes! Due to component tolerances measured values may vary!

www.inotec-licht.de



2023.10.21

Name	Accessories	Art. no.
Cable suspension SN 8400 sq, RAL 9016	optional	101445731
Chain suspension SN 8400 rd, RAL 9016	optional	101445529
J - ET 9 / 24 SV -max.24VDC,320mAconst	Ersatzteil	101420267
LM 39x39 1(12V)/4K KB150	Ersatzteil	104556401