




LED safety luminaire with optimised light distribution for the illumination of escape routes. Housing made of powder-coated aluminium for ceiling mounting with optional cable entry at the side. Incl. 4-chip LED illuminant for maximum safety.



### Technical data

<b>Material:</b>	die-cast aluminum powder-coated	<b>Nominal current DC:</b>	80 mA
<b>Illuminant:</b>	1 x 0,9W LED-module	<b>Protection class:</b>	III
<b>Luminous flux:</b>	139 lm	<b>Input terminals:</b>	2.5mm <sup>2</sup> feed through wiring
<b>Nominal voltage DC:</b>	24 V ±20 %	<b>Temperature ta:</b>	-15...+40 °C




Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

[m]	⊘	⊘	⊘	⊘
2.5	6.8	17.0	5.3	1.9
3.0	5.3	18.1	5.4	1.8
3.5	4.8	17.9	5.4	1.6
4.0	3.8	17.3	5.3	1.3
4.5	3.0	14.3	5.0	0.9

### Articles


#### SN 8424 -03 ALB LED 24V round

Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102063396	101356916	101357017
ceiling mounting	Light colour: 4000 K		Protection category: IP40




#### SN 8424 -03 ALB LED 24V square

Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102063703	101357724	101357825
ceiling mounting	Light colour: 4000 K		Protection category: IP40




#### Chain suspension SN 8424 rd, RAL 9016

Art. no. 101445933



#### Chain suspension SN 8424 sq, RAL 9016

Art. no. 101446135



<b>Name</b>	<b>Accessories</b>	<b>Art. no.</b>
Chain suspension SN 8424 rd, RAL 9016	optional	101445933
Chain suspension SN 8424 sq, RAL 9016	optional	101446135