




LED safety luminaire with optimised light distribution for the illumination of small areas such as lavatories or electrical operating rooms with a luminaire. Housing made of powder-coated aluminium for ceiling mounting with optional cable entry at the side. Incl. 4-chip LED illuminant for maximum safety.



Technical data

Material:	die-cast aluminum powder-coated	Nominal current DC:	80 mA
Illuminant:	1 x 0,9W LED-module	Protection class:	III
Luminous flux:	146 lm	Input terminals:	2.5mm ² feed through wiring
Nominal voltage DC:	24 V ±20 %	Temperature ta:	-15...+40 °C



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8


[m]	1.0lx	0.5lx
2.5	3.3	8.2
3.0	3.5	8.8
3.5	3.6	9.4
4.0	3.5	9.8
4.5	3.2	10.0
5.0	2.7	10.1

Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8


[m]	1.0lx	0.5lx
2.5	2.2	6.8
3.0	2.3	7.4
3.5	2.5	8.0
4.0	2.6	8.4
4.5	2.5	8.6
5.0	2.4	8.2

Articles

SN 8424 -03 SLB LED 24V round			
Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102063905	101358128	101358229
ceiling mounting	Light colour: 4000 K		Protection category: IP40





SN 8424 -03 SLB LED 24V square			
Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102064107	101358532	101358633
ceiling mounting	Light colour: 4000 K		Protection category: IP40



Chain suspension SN 8424 rd, RAL 9016 Art. no. 101445933

Chain suspension SN 8424 sq, RAL 9016 Art. no. 101446135



Name	Accessories	Art. no.
Chain suspension SN 8424 rd, RAL 9016	optional	101445933
Chain suspension SN 8424 sq, RAL 9016	optional	101446135