




LED safety luminaire with optimised light distribution for the illumination of escape routes with high mounting heights. Also suitable for illumination of firefighting and fire alarm systems as well as first aid stations with 5 lx vertical illuminance. Housing made of powder-coated aluminium for ceiling mounting with optional cable entry at the side. Incl. 4-chip LED illuminant for maximum safety.



Technical data

Material:	die-cast aluminum powder-coated	Effective power:	2,8 W
Illuminant:	1 x 1,8W LED-module	Protection class:	III
Luminous flux:	287 lm	Input terminals:	2.5mm ² feed through wiring
Nominal voltage DC:	24 V ±25 %	Temperature ta:	-15...+40 °C
Nominal current DC:	115 mA		





Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

Beam diameter [m]	5.0	6.5	16.0	5.8	1.9
6.0	7.0	17.2	5.2	2.1	
7.0	7.3	18.4	5.5	2.3	
8.0	7.3	19.5	5.8	2.4	
9.0	6.8	20.3	6.2	2.4	
10.0	6.0	20.7	6.5	2.4	
11.0	5.4	20.7	6.7	2.2	
12.0	4.2	20.0	6.8	0.7	

Articles



SN 8424 -06 AHB LED 24V round			
Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102063400	101357118	101357219
ceiling mounting	Light colour: 4000 K		Protection category: IP40

SN 8424 -06 AHB LED 24V square			
Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102063804	101357926	101358027
ceiling mounting	Light colour: 4000 K		Protection category: IP40



Chain suspension SN 8424 rd, RAL 9016 Art. no. 101445933

Chain suspension SN 8424 sq, RAL 9016 Art. no. 101446135



Name	Accessories	Art. no.
Chain suspension SN 8424 rd, RAL 9016	optional	101445933
Chain suspension SN 8424 sq, RAL 9016	optional	101446135
ILD 24/4-CC-320-C	spare part	101425321
LM 39x39 1(6V)/4K KB150 LED Modul	spare part	104556704