




LED safety luminaire with optimised light distribution for the illumination of areas with high mounting heights. Housing made of powder-coated aluminium for ceiling mounting with optional cable entry at the side. Incl. 4-chip LED illuminant for maximum safety.



Technical data

Material:	die-cast aluminum powder-coated	Nominal current DC:	190 mA
Illuminant:	1 x 3,5W LED-module	Protection class:	III
Luminous flux:	545 lm	Input terminals:	2.5mm ² feed through wiring
Nominal voltage DC:	24 V ±20 %	Temperature ta:	-15...+40 °C



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

Beam diameter [m]	Beam diameter [m]	Beam diameter [m]
6.0	6.9	17.5
6.5	7.0	18.1
7.0	7.1	18.6
7.5	7.1	19.0
8.0	6.9	19.3
8.5	6.7	19.6
9.0	6.3	19.8
9.5	5.8	20.0
10.0	5.2	20.1


Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8

Beam diameter [m]	Beam diameter [m]	Beam diameter [m]
6.0	4.9	14.2
6.5	5.1	14.7
7.0	5.0	14.9
7.5	4.9	16.2
8.0	4.7	16.3
8.5	4.7	16.8
9.0	4.6	17.5
9.5	4.5	17.7
10.0	4.3	16.6

Articles


SN 8424 -12 SHB LED 24V round

Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102063295	101356714	101356815
ceiling mounting	Light colour: 4000 K		Protection category: IP40




SN 8424 -12 SHB LED 24V square

Colors	RAL 9005	RAL 9016	RAL (special)
Art. no.	102063602	101357522	101357623
ceiling mounting	Light colour: 4000 K		Protection category: IP40




Chain suspension SN 8424 rd, RAL 9016

Art. no. 101445933



Chain suspension SN 8424 sq, RAL 9016

Art. no. 101446135



Name	Accessories	Art. no.
Chain suspension SN 8424 rd, RAL 9016	optional	101445933
Chain suspension SN 8424 sq, RAL 9016	optional	101446135